

DAP Alex Plus Caulk with silicone

Superior quality, multi-purpose acrylic latex caulk plus silicone. Highly flexible and durable. Excellent adhesion. Cured caulk is mildew resistant. Interior/exterior use. Paintable. Water clean-up. 35 year durability guarantee. Exceeds ASTM specification C 834. Sealing around wood, vinyl, and aluminum siding & trim, caulking around windows and doors 10.1 fl oz.



0119010 Clear
0119011 White

DAP Dynaflex 230 Elastomeric Latex Sealant

Superior flexibility, durability, easy tooling, paintability and low odor. Excellent adhesion and watertight, weatherproof seal; mildew resistant when cured. Water clean-up, 50-year durability guarantee.



0110336 White 10.1 fl oz.
0110337 Clear 10.1 fl oz

GE 45 Year Acrylic Caulk

General-purpose acrylic caulk. Paintable. Cured sealant is mildew resistant. Adheres to wood, metal, plastic, and concrete. 10.1 oz.



0119009 White
0119008 Clear

Pro Flex® Tripolymer Caulking Sealant

Single component, high performance elastomeric sealant. Super flexible, excellent adhesion even when damp, UV resistance, mildew resistant, resealable, may be applied over itself, asphalt compatible, paintable, no dirt pickup; easy to apply, non-stringing formula. 10 fl. oz.



0110383 Crystal Clear

Silicone Caulk

100% silicone caulk provides weatherproof and waterproof seal. Remains flexible and lasts for years under extreme temperature changes, moisture, weathering, vibration, expansion and contraction. Bonds to metal, glass, porcelain, ceramics, wood, fiberglass, many plastics and concrete. 10.3 oz.



0112004 Clear
0112005 White
0112006 Black
0112008 Almond

Painters Caulk

Single component, non-sag, guns easily. Flexible with excellent adhesion to common building materials. Minimal shrinkage. Tack free in 30 minutes. UV stable. Soap and water clean-up. 25-years life expectancy. 10 fl oz.



0119007 White

Skylight Sealant/Caulk

A non-skinning, high-quality, flexible, butyl gunnable sealant for splice joints, exterior perimeters, end dams and glazing seals. It is designed for use on working and nonworking joints, most substrates and non-exposed curtainwall joints. Excellent resistance to UV. Not intended for water immersion. Meets the requirements of Federal Specification TT-S-001657.



0110390 Black

DAP Window Glazing/Caulk


Smooth, easy-working compound for glazing wood, metal, and aluminum sash. Resists cracking, sagging, and chalking. Gun grade. 10.1 fl oz.



0110365 White

Acryl-R Narrow Joint Sealant

One-component solvent release sealant to seal mechanically fixed joints such as corner joints, flashing joints, screw heads and hidden wall system joints.



Excellent adhesion and weatherability. Apply with standard caulking gun. 11 oz.

0112410 Aluminum

DAP Kwik Seal Tub & Tile Caulk

Bonds like a glue and seals like a caulk. Provides a durable, watertight seal, excellent adhesion and flexibility. Tools easily, paintable, water clean-up.

- 0119000** Almond 6 oz
- 0119002** White 6 oz
- 0119001** White 10.1 oz



Dyco C-10 Hypalon Flow Seal Caulk

Self-leveling, paintable, fast drying, weather resistant, will not surface harden or crack. Resists mold and mildew, fungus and bacteria. When cured, resists water, oil, grease, gasoline and many other chemicals. Forms a tough, flexible synthetic rubber seal, dries in 30 to 60 minutes. Second coats can be applied after 30-60 minutes. Semi-gloss sheen. Recommended for horizontal surfaces such as roofs on RVs, mobile homes, metal buildings, roofovers, vents, seams, inside gutters, etc. Easy cleanup with xylene solvent.

- 0110450** Gray 11 oz. tube.
- 0110451** White 11 oz. tube.



GE Firestop

Firestop Silicone

Joint sealant designed to stop the passage of smoke, water and dust for a specified period of time when installed in accordance with independently tested and classified firestop system requirements. Up to 25% movement in a fire-rated joint. **Firestop silicone standards** - UL2079, UL723 ASTM E84

- 0119025** GE6700, Limestone color

Firestop Intumescent

Water-based, is intended to use in UL classified through-penetration firestop systems. **Intumescent standards** - ASTM E814/UL1479 ASTM E84/UL723 Polystyrene foam, Wood, PVC, Steel, and concrete.

- 0119026** GE6701 Pale red color



Caulking Gun

Use with cartridges. Spring grip maintains steady pressure and even bead.

- 0112401**



Caulk Finisher

Scoops away excess caulk for a professionally finished joint. Works with all types of caulks and silicone sealers. Can be trimmed to desired bead for a variety of jobs.

- 0112402**



Boss Biggie Abrasive Wipes

A tub of 80, 8" x 12", dual-sided (abrasive on one side, smooth on the other) cleaning wipes.

- 0181401**



Sta'-Put Spray Adhesive

Sta'-Put Spray Adhesive

Works well on bottom board, vinyl tops, metal or vinyl trim, styrofoam, foam rubber, glass, plastics and much more. Gives high solids, water-resistant bonds offering quick tack, non-wrinkling and flexibility.

- 0110250** 16 oz.; 12/Ctn.
- 0110253** 40# Canister

Sta'-Put High Temp Adhesive

For use where high temperatures are an issue. Flame resistant to approx. 225° F. Non-flammable after tacked. Welds onto surface after about one minute. Not as tacky to the touch, but offers a much stronger bond once cured.

- 0110256** 12/Ctn.

Sta'-Put II Spray Adhesive

Spray directly onto polystyrene safely with no melt-down. Ready to bond in four minutes. Water resistant. Especially formulated for styrofoams.

- 0110252** 13 oz.; 12/Ctn.



Liquid Nails

Premium rubber-based adhesive bonds with virtually all materials, including wood, steel, plaster and concrete. Waterproof. Shear strength exceeding 400 psi — twice the strength of most other adhesives in a similar class. 10.5 oz.

- For Interior Projects **0110255**
- For Subfloors (Exterior) **0110257**
- For Tubs and Surrounds **0110258**
- For Tubs and Surrounds VOC Compliant **0110259**

