

DAP Kwik Seal Tub & Tile Caulk

Bonds like a glue and seals like a caulk. Provides a durable, watertight seal, excellent adhesion and flexibility. Tools easily, paintable, water clean-up.

- 0119000** Almond 6 oz
- 0119002** White 6 oz
- 0119001** White 10.1 oz



Dyco C-10 Hypalon Flow Seal Caulk

Self-leveling, paintable, fast drying, weather resistant, will not surface harden or crack. Resists mold and mildew, fungus and bacteria. When cured, resists water, oil, grease, gasoline and many other chemicals. Forms a tough, flexible synthetic rubber seal, dries in 30 to 60 minutes. Second coats can be applied after 30-60 minutes. Semi-gloss sheen. Recommended for horizontal surfaces such as roofs on RVs, mobile homes, metal buildings, roofovers, vents, seams, inside gutters, etc. Easy cleanup with xylene solvent.

- 0110450** Gray 11 oz. tube.
- 0110451** White 11 oz. tube.



GE Firestop

Firestop Silicone

Joint sealant designed to stop the passage of smoke, water and dust for a specified period of time when installed in accordance with independently tested and classified firestop system requirements. Up to 25% movement in a fire-rated joint. **Firestop silicone standards** - UL2079, UL723 ASTM E84

- 0119025** GE6700, Limestone color

Firestop Intumescent

Water-based, is intended to use in UL classified through-penetration firestop systems. **Intumescent standards** - ASTM E814/UL1479 ASTM E84/UL723 Polystyrene foam, Wood, PVC, Steel, and concrete.

- 0119026** GE6701 Pale red color



Caulking Gun

Use with cartridges. Spring grip maintains steady pressure and even bead.

- 0112401**



Caulk Finisher

Scoops away excess caulk for a professionally finished joint. Works with all types of caulks and silicone sealers. Can be trimmed to desired bead for a variety of jobs.

- 0112402**



Boss Biggie Abrasive Wipes

A tub of 80, 8" x 12", dual-sided (abrasive on one side, smooth on the other) cleaning wipes.

- 0181401**



Sta'-Put Spray Adhesive

Sta'-Put Spray Adhesive

Works well on bottom board, vinyl tops, metal or vinyl trim, styrofoam, foam rubber, glass, plastics and much more. Gives high solids, water-resistant bonds offering quick tack, non-wrinkling and flexibility.

- 0110250** 16 oz.; 12/Ctn.
- 0110253** 40# Canister

Sta'-Put High Temp Adhesive

For use where high temperatures are an issue. Flame resistant to approx. 225° F. Non-flammable after tacked. Welds onto surface after about one minute. Not as tacky to the touch, but offers a much stronger bond once cured.

- 0110256** 12/Ctn.

Sta'-Put II Spray Adhesive

Spray directly onto polystyrene safely with no melt-down. Ready to bond in four minutes. Water resistant. Especially formulated for styrofoams.

- 0110252** 13 oz.; 12/Ctn.



Liquid Nails

Premium rubber-based adhesive bonds with virtually all materials, including wood, steel, plaster and concrete. Waterproof. Shear strength exceeding 400 psi — twice the strength of most other adhesives in a similar class. 10.5 oz.

- For Interior Projects **0110255**
- For Subfloors (Exterior) **0110257**
- For Tubs and Surrounds **0110258**
- For Tubs and Surrounds VOC Compliant **0110259**

