



CPDS 1000 System

Constant Pressure Dispensing System



Tanks sold separately.

The Touch 'n Seal CPDS 1000 is an inexpensive, low maintenance dispensing mechanism that, when used according to manufacturer's directions, applies Class 1 fire retardant, thermal insulating and sound attenuating 2-component polyurethane spray foam.

Height	49 in (125 em)
Depth	33 in (84 em)
Width	24.5 in (62 em)
Foam Delivery Rate @ 160 psi	4.0 lbs (1.8 kg) / minute
Foam Delivery Rate @ 200 psi	5.5 lbs (2.5 kg) / minute
Maximum Hose Length	150 ft (46 m)
Power Source	120V, 15 amp
Alternate Power Sources	Pressurized Dry Nitrogen, Compressed Air
Foam Type	CP 750 FR, 2 Component, Fire Retardant, 1.75 PCF CP 1200 FR, 2 Component, Fire Retardant, 1.0 PCF

- 0112150** Dispensing System
- 0112151** Closed Cell Foam Tank

Two-Component Polyurethane Foam Kits

Portable, disposable and self-contained with color-coded, pre-connected hoses. These kits are available in sizes from 15-600 board feet and provide a quick consistent flow of foam that dries in under a minute. Foam expands 30X.

Touch 'n Seal Two Component Foam Kits are portable, self-contained dispensing systems. When used according to manufacturer's directions, these systems supply thermal insulating and sound attenuating 2-component polyurethane

spray foams. Touch 'n Seal spray foams are permanent and dry within minutes of application.

Touch 'n Seal Spray Foam Kits use disposable, pressurized chemical cylinders to dispense polyurethane spray foams eliminating the need for external air compressors, pumping equipment or dry nitrogen. These systems provide quick and easy foam application for repairs and renovations, new installations and production applications.



2-Component spray foam systems provide fast, even foam flow that cures in about 45 seconds, making it ideal for use on large gaps and on all surfaces.

Foam kits include applicator gun and 10' hose, and illustrated directions. Kits are self contained, portable, and disposable. Contains no CFC's, no urea formaldehyde.

Standard

- 0112119** 2 Part, 15 Board Feet
- 0112101** 2 Part, 110 Board Feet
- 0112102** 2 Part, 200 Board Feet
- 0112104** 2 Part, 600 Board Feet

Fire Retardant

- ASTM E84 rating: flame spread 15, smoke developed 10.
- 0112107** 2 Part, 200 Board Feet
- 0112108** 2 Part, 600 Board Feet

Replacement Nozzles

- 0112131** L Fan Nozzle Kit, Yellow 25/Box
- 0112132** Conical Nozzle Kit, Clear 25/Box

Handi Tools



FOMO

0112025 H300 dispensing gun, with plastic handle.



FOMO

0112026 H500 Dispensing Gun, Steel Handle and Tip.



FOMO

0112027 H700 dispensing gun, steel replaceable parts.

0112024 Plastic Disposable Extension Tips For Dispensing Guns. Used for accessing very small cracks and crevices. 5/Bag

Replacement Nozzles

0112031 Fan Spray Nozzle 8/Pk.

0112032 Cone Spray Nozzle 8/Pk.

Handi Foam Polyurethane Sealant

FOMO

Polyurethane foam sealants are moisture-cured, designed to completely fill and seal small gaps, cracks and voids. This one-component polyurethane is used in a bead application.

0112019 Tank only 7128 bead ft., (I-160)

0112018 Tank w/accs. 8688 bead ft.,(I-160)

0112038 Tank only 11406 bead ft.,(I-260)

0112039 Tank w/accs. 13914 bead ft.,(I-260)

0112021 24 oz.,(680-G)

0112029 25' Hose assembly



Handi Stick

Handi-Stick® Polystyrene Construction Adhesive is a onecomponent polyurethane foam adhesive specifically designed for adhering expanded and/or extruded polystyrene, foundation insulation systems, and Insulated Concrete Forms (ICFs). The unique product properties, performance and professional application system gives Handi-Stick® Polystyrene Construction Adhesive many advantages over traditional caulks.

0112009 24 oz.

FOMO



Handi Foam

Polyurethane Sealant with straw applicator.

FOMO

0112023 12 oz.

0112012 20 oz.

0112011 29 oz.

0112021 24 oz. .



Handi Cleaner

Handi Cleaner cleaning agent, used to dissolve uncured or fresh polyurethane foam as well as dispensing guns.

FOMO

0112014 12 oz.



Handi Foam Quick Cure Spray Foam

Fomo's disposable foam kits are chemically cured, two-component polyurethane froth foam kits, designed to fill large voids and surfaces. Cures in minutes. Kits are packaged with the patented Handi-Gun®.

FOMO

0112015 Covers 205 Bd Ft

0112016 Covers 105 Bd Ft

0112017 Covers 605 Bd Ft

0112042 Covers 22 Bd Ft



Handi Foam E-84 Class 1

- Meets building code requirements for class 1 materials.

- **0112037** Handi Foam E-84 Class 1 FS25 Contains flame retardants in order to meet the testing requirements of ASTM E-84, a Flame Resistance Rating. This foam is not fire proof. Covers 105 Bd Ft.

FOMO

- **0112045** 2 Part w/Retardant E-84, 205 BF (P10726)

Handi Foam Fire Block **FOMO**



Closed cell polyurethane sealant, provides an R-value of 4-5/inch. Orange colored for easier ID by codes officials.

0112022 Handi Foam® Fireblock Sealant. Pressurized Can, Requires Dispensing Gun. 24 oz.



Handi Seal® Window & Door Sealant

The Dry-Seal Technology™ is the only patented formula designed to prevent moisture and mold problems by repelling water.

0112013 Requires Dispensing Gun, 24 oz. Pressurized Can

0112020 With Straw Applicator, 24 oz. Pressurized Can

FOMO