

Insulation Blowers

INSULATION BLOWERS COME COMPLETE WITH:

100 feet of 3 inch blowing hose, One 3 inch stainless steel hose connector, Three 3 inch stainless steel hose clamps, Two 100 foot power cords, 100 foot dual remote control, Variable speed blower pressure control, Airlock stainless steel inserts, Pinset material slide gate

Wasp

Compatible with fiberglass (510 lbs per hr), cellulose (1800 lbs per hr), and rockwool insulations. Lightweight and durable polyethylene construction. Wheels for portability. Fewer moving parts for less maintenance and downtime. Low amp draw. Emergency stop button.



0380410

FORCE/2

- Professional Grade – Virtually Indestructible!
- With an 8½ cu. ft. hopper that can hold 50 lbs of material, a strong 1½ hp motor and a powerful 3.6 PSI blower. Blows up to 2,012 lbs of light density cellulose and 428 lbs of fiberglass per hour. Now available with 4.5 PSI, 116 CFM blower. Easy setup, operation and cleanup.



0380453

FORCE/3

- High production at 2520 lbs of cellulose & 1350 lbs of fiberglass per hour. Portable. Dual blowers. 3.0 or 4.0 PSI. Long life seals



0380454

Blower Accessories:

Hose:

- 0380422** 2" MARK II Clear Hose X 50'
0380423 2-1/2" MARK II Blue Hose X 50'
0380424 3" MARK II Clear Hose X 50'

Swivels:

- 0380425** 2" Hose Swivel
0380426 2-1/2" Hose Swivel
0380427 3" Hose Swivel

Misc. Accessories:

- 0380415** 2" to 1" Wall Nozzle
0380416 1-1/4" x 10' Wall Tubing
0380417 3" to 2-1/2" Reducer
0380418 2-1/2" to 2" Reducer
0380419 3" SS Hose Clamp
0380420 2-1/2" SS Hose Clamp
0380421 2" SS Hose Clamp

Pine Wood Plugs

Slightly tapered for easy insertion. The top 1/8 is the full diameter measurement for a tight even fit. Made from kiln dried lumber. Packaged in 250 count bags.

- 0270427** 1"
0270428 2"
0270434 2-1/2"
0270435 2-9/16"



Long-Barrell Plst Plugs

The Long Nose, with its exceptional design, is our best plastic plug. With a 5/8" shank and heavy gripping teeth, this plug will hold in both single and multiple layers of siding. 250 per bag. 2000 per box.

- 0270425** 1"
0270426 2"
0270424 2-1/2" (regular nose)



Foam Drywall Plugs

Styrofoam plugs used for holes in drywall- recessed to accept spackling compound. They absorb little moisture, thus require fewer layers of spackling for a smooth finish. 1000 per package.

- 0270429** 1"
0270430 2"
0270432 2-1/2"
0270433 2-9/16"



Durovent Baffle

The DUROVENT BAFFLE is both water resistant and durable, blocking out moisture and wind from penetrating the attic, satisfying even the most demanding building code requirements. The DUROVENT BAFFLE is designed to friction fit between the rafters or trusses with the vent's cones pushed up against the roof deck. Secure the vent in place stapling the wide nailing flanges to the truss and top plate by using a horizontal stroke with your hammer tacker. 23.5" x 46"



- 0270445** 50/bag
0270446 70/bag

TVM Vent Panels

- Double vent panel
- Designed for 24" on center
- Perforated for 16" on center
- No hassles with utility knives



0270449 50/bag

rFoil HVAC Duct Insulation and Tape

rFOIL™ Duct Insulation is a double layer of polyethylene bubbles sandwiched between two highly reflective radiant barriers. This inspector-friendly tape means no hassles at the job site, and peace of mind for installers. Prevents condensation.



rFoil

- 0270529** 4' x 100'
0270531 3' x 100'

Tape

- 0270532** 4' x 125'
0270534 4' x 50'
0270530 2.5" x 180' roll