

Infrared Cameras

FLIR infrared cameras give you the power to see the invisible. With a FLIR camera, you can see and document the telltale temperature differences that show moisture damage, missing insulation, air infiltration, and many other building problems faster than any other technology.



Specifications	Point and Shoot				
Stock #	0380004	0380006	0380001	0380002	380003
Model Number	i5	i7	b40	b50	b60
Imaging Specifications					
Resolution	80 × 80	120 × 120	120 × 120	140 × 140	180 × 180
Total Pixels	6,400	14,400	14,400	19,600	32,400
Thermal Sensitivity	<0.1°C	<0.1°C	<0.1°C	<0.09°C	<0.07°C
Uncooled Microbolometer (made in USA)	x	x	x	x	x
Accuracy	+/-2% or 2°C	+/-2% or 2°C	+/-2% or 2°C	+/-2% or 2°C	+/-2% or 2°C
Object Temperature Range	-4°F to 482°F (-20°C to 250°C)	-4°F to 482°F (-20°C to 250°C)	-4°F to 248°F (-20°C to 120°C)	-4°F to 248°F (-20°C to 120°C)	-4°F to 248°F (-20°C to 120°C)
High Temp Settings					32°F to 662°F
Lens Options					
Lens Options	17° × 17°	25° × 25°	25° × 25°	25° × 25°	25° × 25°
Zoom					1-2× Continuous Digital
Focus	Focus Free	Focus Free	Manual	Manual	Manual
Color LCD	2.8"	2.8"	3.5"	3.5"	3.5"
Video Camera w/ Lamp			0.6 MP	2.3 MP	2.3 MP
Fusion			Fixed PIP	PIP 3 Size Steps	PIP Scalable
On-Screen Laser Spot			x	x	x
Video Out			Streaming MPEG-4 to PC	Streaming MPEG-4 to PC	Streaming MPEG-4 to PC
Analysis					
Spotmeter	Center Spot	Center Spot	Center Spot	Center Spot	Center Spot
Area		One Box w/ Min./ Max.	One Box w/ Min./ Max.	One Box w/ Min./ Max.	One Box w/ Min./ Max.
Auto Temp Detection					Auto Hot/Cold w/in Areas
Isotherm		Above/Below	Above/Below	Above/Below	Above/Below
Emissivity Correction	Variable 0.1 to 1.0	Variable 0.1 to 1.0	Variable 0.1 to 1.0	Variable 0.1 to 1.0	Variable 0.1 to 1.0
Reflection Correction	Automatic	Automatic	Automatic	Automatic	Automatic
Alarms			Dew Point & Insulation	Dew Point & Insulation	Dew Point & Insulation
Auto Calculation					
Annotation					
Voice (60 seconds)					x
Text					
Sketch					
File Storage					
Radiometric JPG	x	x	x	x	x
MPEG Video Recording					
Other					
Instant Report					
MeterLink					x
ThermaTrak	Optional	Optional	Optional	Optional	Optional

Infrared Cameras

FLIR's new professional infrared cameras expand the choices available to thermographers and building professionals who need a powerful solution at an affordable price. Higher models in the B-Series family add touch-screen, text, and support of voice recording. These infrared cameras can help professionals identify energy waste and diagnose moisture and other conditions in buildings that can cause damage and loss of business.



Bluetooth Available on models b60 and up.

Specifications	Professional			
Stock #				
Model Number	B200	B300	B360	B400
Imaging Specifications				
Resolution	240 × 180	320 × 240	320 × 240	320 × 240
Total Pixels	43,200	76,800	76,800	76,800
Thermal Sensitivity	<0.07°C	<0.05°C	<0.05°C	<0.05°C
Uncooled Microbolometer (made in USA)	x	x	x	x
Accuracy	+/-2% or 2°C	+/-2% or 2°C	+/-2% or 2°C	+/-2% or 2°C
Object Temperature Range	-4°F to 248°F (-20°C to 120°C)	-4°F to 248°F (-20°C to 120°C)	-4°F to 248°F (-20°C to 120°C)	-4°F to 248°F (-20°C to 120°C)
High Temp Settings	32°F to 662°F	32°F to 662°F	32°F to 662°F	
	(0°C to 350°C) Option	(0°C to 350°C) Option	(0°C to 350°C) Option	(0°C to 350°C) Standard
Lens Options	Standard: 25° × 19°; Optional: 90°, 45°, 15°, 6°; Close-up: 100µ, 50µ			
Zoom	1-2× Continuous Digital	1-4× Continuous Digital	1-8× Continuous Digital	
Focus	Auto & Manual	Auto & Manual	Auto & Manual	Auto & Manual
Color LCD	3.5"	3.5"	3.5"	3.5"
Video Camera w/ Lamp	3.1 MP	3.1 MP	3.1 MP	3.1 MP
Fusion	PIP Scalable	PIP Scalable	PIP Scalable & Moveable	PIP Scalable & Moveable
On-Screen Laser Spot	x	x	x	x
Video Out	Composite Video Streaming MPEG-4 to PC	Composite Video Streaming MPEG-4 to PC	Composite Video Streaming MPEG-4 to PC	Composite Video Streaming MPEG-4 to PC
Analysis				
Spotmeter	Five	Five	Five	Five
Area	Five Boxes w/ Min./Max.	Five Boxes w/ Min./Max.	Five Boxes w/ Min./Max.	Five Boxes w/ Min./Max.
Auto Temp Detection	Auto Hot/Cold w/in Areas	Auto Hot/Cold w/in Areas	Auto Hot/Cold w/in Areas	Auto Hot/Cold w/in Areas
Isotherm	Detect High/Low Temp/Interval	Detect High/Low Temp/Interval	Detect High/Low Temp/Interval	Detect High/Low Temp/Interval
Emissivity Correction	Variable 0.1 to 1.0	Variable 0.1 to 1.0	Variable 0.1 to 1.0	Variable 0.1 to 1.0
Reflection Correction	Automatic	Automatic	Automatic	Automatic
Alarms	Dew Point & Insulation	Dew Point & Insulation	Dew Point & Insulation	Dew Point & Insulation
Auto Calculation	Delta T	Delta T	Delta T	Delta T
Annotation				
Voice (60 seconds)	x	x	x	x
Text			x	x
Sketch			x	x
File Storage				
Radiometric JPG	x	x	x	x
MPEG Video Recording				x
Other				
Instant Report			x	x
MeterLink	x	x	x	x
ThermaTrak	Optional	Optional	Optional	Optional

Heating & Cooling
Coatings & Caulks
Insulation & Accessories
Safety & Protection
Appliances
Venting & Plumbing
Diagnostic Tools
Siding
Putty/Foam Tapes
Windows & Doors
Index

Fluke TiR1 Thermal Imager

SmartView™ analysis and reporting software (with free upgrades through life of product), 2 GB SD Memory Card, SD Card Reader for downloading images into your computer, hard carry case, portable soft carry case, hand strap, rechargeable battery, and AC charger/power supply.

Thermal imaging camera w/20 mm lens, ac power supply/ battery charger (including mains adapters), SD memory card, SD card reader (USB) for downloading images into your computer, SmartView™ software with free software upgrades for life, rugged hard carrying case, soft transport bag, hand strap, users manual, warranty registration card



FLUKE

0380015

EXTECH Borescope/Wireless Inspection Camera

17mm camera diameter and 3.5" color TFT LCD wireless monitor with 2GB micro SD memory card (included) for capturing images (JPEG) or video (AVI) for viewing on your PC,



EXTECH
INSTRUMENTS
A FLIR COMPANY

0380005

Carbon Monoxide {CO} Meter

Air safety checks in all environments. Up to 1000ppm.

Features:

- Auto Zero at start up
- Displays CO levels from 0 to 1000ppm
- 1ppm resolution with ±5% or ±10ppm basic accuracy (whichever is greater)
- Utilizes a stabilized electrochemical gas specific (CO) fast response sensor
- Audible alarm starts at 35ppm
- Memory stores 10 readings
- Ergonomic pocket size housing
- Max Hold and Data hold buttons
- Auto Power off
- Dims: 6.3 x 2.2 x 1.57" (160 x 56 x 40mm); Weight: 6.35 oz. (180g)
- 1 year warranty; CE approved
- Complete with 9V battery, protective holster, and case



EXTECH
INSTRUMENTS
A FLIR COMPANY

0380007

TESTO 881-1 Thermal Imager KIT

- Detector type 160 x 120 pixels
- Good image quality NETD < 50 mK
- High quality standard lens 32° x 23°
- Integrated digital camera
- Auto Hot/Cold Spot Recognition
- Manual focus
- Temperature range -20 to +350°C
- 33 Hz (inside the EU, outside 9 Hz)

Includes:

- Pro software with integrated report creation
- SD card
- USB cable
- Mains unit
- Li-ion rechargeable battery
- Adapter for tripod mounting
- Robust, high-quality case



0380010

Testo 327-1 Combustion Analyzer Kit

The best deal in combustion!

Features:

- Fast 30-second warm-up
- 4-line backlit display (user configurable)
- Rugged single line probe connection
- Integrated protective boot-dishwasher safe
- Built-in magnetic back
- 5 hr. Li-Ion rechargeable battery
- Easily accessible field serviceable sensors
- Pre-programmed with 8 standard fuels

Kit Includes:

- 327-1 analyzer
- 5' Hose & Probe
- Li-Ion Battery
- AC Power Adapter



0380455 Kit

0380458 Kit, plus case and printer

0380456 Case and printer only

Additional EXTECH AND TESTO tools are available by special order. Contact your local Blevins branch. www.blevinsweatherization.com