

## UV Resistant Black Patch & Coat 40777

### Features and Benefits:

- Zero VOC formula.
- Seals and topcoats in one process.
- Guaranteed not to crack or alligator for 5 years.
- Provides a smooth, flexible glossy surface.
- Excellent for all asphalt surfaces.
- No toxic heavy metals.
- UV and weather resistant.
- Soap and water cleanup - while wet.
- Brush grade for easy application.

### Warranty:

- 5 years

### Recommended for:

- Rolled Roofing
- Driveway Cracks
- Auto Underbodies
- Metal
- Slate
- Truck & Trailer Roofs
- Compatible with All Roof Asphaltic Surfaces
- Patching Asphalt / Fiberglass Shingles
- Chimney & Pipe Flashings
- Metal & Wood Gutters
- Composition Roofs



### Coverage per gallon:

(Apply two coats at the rates shown.)

For Coating Surfaces 50 sq.ft.  
Concrete (depends on porosity) 50 sq.ft.

| Item Number           | Size / per Case  | UPC Code        | Ship Weight | Units per Pallet |
|-----------------------|------------------|-----------------|-------------|------------------|
| KSTO <b>40777</b> -99 | 10.5 Oz. / 20    | 0 50926 40778 0 | 17          | 54 Cases         |
| KSTO <b>40777</b> -14 | 29.5 oz          | 0 50926 40774 2 | 42          | 36 Pails         |
| KSTO <b>40777</b> -16 | .9 Gallon / 4    | 0 50926 40771 1 | 38          | 45 Cases         |
| KSTO <b>40777</b> -20 | 4.75 Gallon Pail | 0 50926 40775 9 | 46          | 36 Pails         |



A Business Unit of The Sherwin-Williams Company