

MSDS Document

Product BOSS® 378 RV/Mobile Home Sealant

1. Chemical Product and Company Identification

Trade Name of this Product BOSS® 378 RV/Mobile Home Sealant

Synonyms: 02395CL10, 02395WH10, 02395BK10

MSDS ID BOSS378

Manufacturer

Accumetric, LLC
350 Ring Road
Elizabethtown, KY 42701


Phone Number

(270) 769-3385

Emergency Phone

CHEMTREC (800) 424-9300

Revision Date 12/17/2009



2. Composition and Information on Ingredients

Ingredient	CAS Number	Weight %	ACGIH TLV	PEL	STEL
Methyltriacetoxysilane	4253-34-3	1% - 5%	TWA 10ppm	TWA 10ppm	15ppm
Ethyltriacetoxysilane	17689-77-9	1% - 5%	TWA 10ppm	TWA 10ppm	15ppm

3. Hazard Identification

Primary Routes of Entry

Eye contact, inhalation, skin contact

Eye Contact

Direct contact may cause moderate irritation.

Skin Contact

May cause moderate irritation.

Ingestion

No significant effects expected from a single short term exposure.

Inhalation

Irritates respiratory passages very slightly.

Symptoms of Overexposure

No known applicable information.

Existing Conditions Aggravated by Exposure

No known applicable information.

4. First Aid Information**Eye Contact**

Immediately flush with water for 15 minutes. Seek medical attention.

Skin Contact

Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.

Inhalation

Remove to fresh air. No first aid should be needed.

Ingestion

No first aid should be needed.

Comments

Treat according to person's condition and specifics of exposure.

5. Fire Fighting Measures**Auto-ignition Temperature**

Not determined

Flammability Limits in Air

Not determined

Extinguishing Media

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

Special Fire Fighting Procedures

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire or Explosion Hazards

None known

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the

following hazardous decomposition products:

Carbon oxides and traces of incompletely burned carbon compounds

Formaldehyde

Hydrogen

Silicon dioxide

Metal oxides

Comment

When temperatures above 150°C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limits for formaldehyde.

6. Accidental Release Measures

Steps to be taken in case of spill or release

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

7. Handling and Storage

Handling

Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact.

Storage

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

8. Exposure Controls and Personal Protection

Exposure Controls

Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10

ppm, STEL 15 ppm.

Eye Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:
Silver Shield® 4H®

Respiratory Protection

No respiratory protection should be needed with good local ventilation.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry (www.SEHSC.com).

9. Physical and Chemical Properties

Specific Gravity 1

Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

10. Stability and Reactivity

Chemical Stability

Stable

Hazardous Polymerization

Will not occur

Conditions to Avoid

None known

Materials to Avoid / Incompatibility

Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form.

11. Toxicological Information

Special Hazard Information on Components

No known applicable information.

12. Ecological Information

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

13. Disposal Considerations

Waste Disposal Method

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

14. Transportation Information

DOT Road Shipment Information

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA Title III Section 302 Extremely Hazardous Substances

None

SARA Title III Section 304 CERCLA Hazardous Substances

None

SARA Title III Section 312 Hazard Class

Acute: Yes
Chronic: No
Fire: No
Pressure: No
Reactive: No

SARA Title III Section 313 Toxic Chemicals

Depending on color, may contain:
Alumina hydrate (21645-51-2)

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:
None known

Massachusetts

Silica, amorphous (7631-86-9)

Depending on color, may also contain:

Alumina hydrate (21645-51-2)
Carbon black (1333-86-4)
Titanium dioxide (13463-67-7)

New Jersey

Dimethyl siloxane, hydroxy-terminated (70131-67-8)
Silica, amorphous (7631-86-9)
Methyltriacetoxysilane (4253-34-3)
Ethyltriacetoxysilane (17689-77-9)

Depending on color, may also contain:

Alumina hydrate (21645-51-2)
Carbon black (1333-86-4)
Polydimethylsiloxane (63148-62-9)
Titanium dioxide (13463-67-7)

Pennsylvania

Dimethyl siloxane, hydroxy-terminated (70131-67-8)
Silica, amorphous (7631-86-9)

Depending on color, may also contain:

Alumina hydrate (21645-51-2)
Carbon black (1333-86-4)
Polydimethylsiloxane (63148-62-9)
Titanium dioxide (13463-67-7)

16. Other Information

Disclaimer

The data contained herein is based upon information that Accumetric LLC believes to be

reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements to suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.