

**LN-600**

**Interior**

***A fast bonding, permanent, waterproof adhesive for most common materials.***

**PRODUCT DESCRIPTION**

LIQUID NAILS® Small Projects & Repairs Adhesive, LN-600, is a fast-bonding, permanent, waterproof adhesive formulated for most common materials. This is the original formula of LIQUID NAILS Adhesive in a handy 4 oz. squeeze tube size, so it can work where a hammer and nails can't. Resealable cap keeps product fresh.

**RECOMMENDED FOR**

- Wall tile
- House numbers
- Vinyl cove base
- Concrete
- Brick veneer
- Countertops
- Soap dishes
- Wood
- Drywall patches
- Stone
- Ceramics
- Metals
- Towel racks
- Corkboard
- Aluminum
- Carpeting
- Shelving
- Moldings

**NOT RECOMMENDED FOR**

- Sheet goods
- Wood flooring
- Ceiling applications
- Underwater applications

*Please research all installation instructions and read entire label for safety, health & environmental information prior to use.*

Look for other LIQUID NAILS products which are right for your specific project.

**PRODUCT ADVANTAGES**

- Fast-bonding
- Permanent
- Waterproof
- Resealable cap
- Works where hammer & nails can't
- Up to 20 minutes working time
- Convenient, easy-to-use squeeze tube

**DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPORS MAY CAUSE FLASH FIRE.**

Read Label and Material Safety Data Sheet Prior to Use.  
See other cautions on last page. MDSF3-1100



## **SURFACE PREPARATION**

Surfaces must be clean, dry and structurally sound. Apply in well-ventilated area.

## **APPLYING THE PRODUCT**

This product sets up quickly, yet allows repositioning for up to 20 minutes after application. Allow approximately 24 hours for adhesive to dry.

**Carpeting:** Keep loose carpet edges down by applying a bead of adhesive to carpet back. Use sparingly for easy carpet removal later on.

**Ceramic and other tile:** For mirror tiles, apply a ribbon of adhesive to back of tile and press firmly into place. For decorative tiles, wall inlay panels or cork tiles, apply 3 or 4 ribbons of adhesive to wall and press tile into place. Heavy tile may require bracing for 24 hours.

**Wood:** Apply a bead of adhesive to the back of trim and press into place. For wood strips, apply 2 ribbons of adhesive to the back of each strip and press into place.

**Countertops:** Secure peeling countertops by applying adhesive to base and pressing firmly. Use a clamp to temporarily hold the countertop in place.

**Drywall:** To serve as a backing for drywall patches, adhere strips of wood 3" longer than the hole behind the opening with adhesive and allow to dry 24 hours. Then use adhesive to affix properly sized patch to the wood backing strips and finish edges in the conventional manner.

**Vinyl cove base:** Apply 2 beads of adhesive to back and press firmly to wall.

**Shelving:** Apply a bead of adhesive to back of brackets. Press brackets firmly against wall. Pull assembly apart and let air-dry for 5–8 minutes, allowing the adhesive to set. Press brackets back into place and hold with masking tape for 48 hours. Please note some fasteners may need to be used.

**Working time:** Sets up quickly, yet allows repositioning up to 20 minutes after application. Allow approximately 24 hours to dry.

## **CLEAN-UP**

Use *LIQUID NAILS™ Adhesive & Caulk Remover* or mineral spirits.

## **DISPOSAL**

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants. EAD-C9

## **LIMITED WARRANTY**

Satisfaction guaranteed when handled and applied according to label instructions. Labor and cost of labor are excluded. Call 1-800-634-0015 for warranty details. This warranty gives specific legal rights, which may vary from state to state.

### **DANGER! EXTREMELY FLAMMABLE.**

**CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.**

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Keep away from heat, sparks and flame. **Do not smoke. Vapors may ignite explosively.** Vapors may spread long distances. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Do not breathe vapors. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and skin. Close container after use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil, then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical attention. **For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.** MDS63-1006

## **LN-600**

### **TECHNICAL INFORMATION**

**Base:** Synthetic rubber and resin

**Type:** Solvent elastomeric adhesive

**Color:** Light tan

**Appearance:** Smooth paste

**Application Temperature:** 20° to 100° F

(-7° to 38° C) Do not use with Styrofoam® over 90° F (32° C)

**Service Temperature:** -20° to 140° F

(-29° to 60° C)

**Adhesion:** Excellent to most common building materials

**Consistency:** Squeeze tube grade

**Bridging Ability:** Very good

**Extrudability:** Good

**Shear Strength:** 24 hours - 250 psi

48 hours - 350 psi

28 days - Exceeds 400 psi

**Durability:** Very good

**Flexibility:** Very good

**Water Resistance:** Very good

**Ageing:** Remains flexible up to 25 years

**Freeze-Thaw-Stable:** Does not freeze

**Bleed:** None

**Staining:** May stain real or cultured marble & granite

**Odor:** Mild solvent

**Drying Time:** Suitable for use after 24 hours

**Working Time:** 15 minutes

**Weight Per Gallon:** 9.8 pounds (1.17 kg/l)

**Viscosity:** 220,000 CPS

**Volatiles:** 35%

**Solids:** 65%

**Flammability:** Extremely flammable; non-flammable when dry

**Flash Point:** 4° F (-16° C)

**Shelf Life:** 12 months from date of purchase

**MAX VOC:** 409 GPL

**Specifications:** ASTM C-557



15885 West Sprague Rd.  
Strongsville, OH 44136

[www.liquidnails.com](http://www.liquidnails.com)

Customer Service 1-800-634-0015