



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 6/21/10

DAP® DYNAFLEX 230® Premium Indoor/Outdoor Sealant - Clear

- Exceeds ASTM C 920, Class 25
- Waterproof and paintable
- Outstanding durability and adhesion
- Crack proof
- Cured sealant is mold & mildew resistant
- Permanently flexible
- Easy water clean-up
- Seals out insects
- Paintable
- Improves energy efficiency
- Low VOC content

Packaging: 10.1 fl. oz. (300 mL) cartridge, 5.5 fl. (162 mL) oz. squeeze tube
Color: Clear
UPC Number: 70798 18305, 70798 74120, 70798 18357

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert".
Order Information: 800-327-3339
Fax Number: 410-534-2650

Product Description:

DAP® DYNAFLEX 230® PREMIUM WATERPROOF & PAINTABLE SEALANT combines outstanding durability, adhesion and flexibility with easy tooling, paintability, low odor and water clean up. Indoor/outdoor use. Ideal for sealing out air leaks to improve energy efficiency.

Suggested Uses:

Ideal for Caulking and Sealing:

- | | | |
|---------------------|-----------------|-------------------------|
| • Windows and doors | • Pipes | • Siding and trim |
| • Moldings | • Butt joints | • Tuck-pointing |
| • Baseboards | • Corner joints | • Other gaps and cracks |
| • Vents | | |

Outstanding Adhesion to:

- | | | |
|-----------------------|-----------|-----------------|
| • Wood | • Metal | • Brick |
| • Aluminum | • Glass | • Concrete |
| • Vinyl | • Masonry | • Most plastics |
| • Plaster and drywall | • Stucco | • Stone |
| • Painted surfaces | | |

Performance Characteristics:

- Meets the requirements of ASTM C 920 standard specification for Elastomeric joint sealants, Type S, Grade NS, Class 25. Use NT, G, A and M.
- Meets the performance specifications of Federal Spec TT-S-00230c (COMNBS0), Type II, Class A.
- Exceeds ASTM Spec C 834 Standard Specification for Latex Sealants.
- Tack free in 30 minutes.
- Paintable with latex or oil-based paints.
- Easy water clean-up.

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old caulk, dirt, dust, and grease.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size. Puncture inner foil seal (cartridge).
3. Load into caulking gun if using the cartridge.
4. Fill gap with sealant, pushing sealant ahead of nozzle.
5. For a neat finish, smooth bead of sealant with a finishing tool.
6. Clean up excess sealant with a damp cloth before it skins over (15 minutes).
7. Allow sealant to dry clear before painting with latex or oil-based paints.
8. Reseal tube/cartridge for storage and reuse

For Best Results:

- Apply in temperatures above 40°F (4,44 °C).
- Do not apply if rain or freezing temperatures are forecasted before total cure can occur. Cold weather and high humidity will slow down cure time.
- Do not use below waterline or for marine or automobile applications, or filling surface defects.
- Joint depth should not exceed 1/2” (1,30 cm) wide by 1/2” (1,30 cm) deep. If joint exceeds 1/2” (1,30 cm) deep use foam backer rod.
- **Applies white, dries clear in 7-14 days. Sealant should not be painted until it has turned clear.**
- Store sealant away from extreme heat or cold.

Physical & Chemical Characteristics:

Tooling Time:	10 Minutes
Tack-Free Time:	30 Minutes
Dynamic Joint Movement:	± 25%
Paintable:	Yes
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Advanced Acrylic Polymer
Volatile:	Water
Flash Point:	None
Filler:	None
Density:	1.07 ± 0.01
Solids:	57.0% ± 1.0% by weight
Weight per Gallon:	8.90 ± 0.05 lbs./gal. (1,066 kg/L+/- 0,0005 kg/L)
Temperature Service Range:	-30°F to 180°F (- 34,50 to 82,20 °C)
Temperature Application Range:	40°F to 100°F (4,44 to 37,78 ° C)
Freeze Thaw Stability:	Passes 5 Cycles 0°F to 70°F (- 17,78 °C to 21.1 °C)
Shelf Life:	12 Months

Coverage: 5.5 fluid ounces: 30 linear ft. at a 3/16" diameter bead (9,14 m at a 0,47 cm bead size) 10.1 fluid ounces 55 linear ft. at a 3/16" bead size. (16,76 m at a 0,47 cm bead size)

MSDS No: 00010020001 (U.S.)
00010001605 (Canada)

Clean Up:

Clean up excess uncured sealant with a damp cloth or sponge before it skins over. Wash hands with warm water and soap. Dried material must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet for safety information. You can request an MSDS sheet by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

50-Year Satisfaction Guarantee (U.S.):

If not satisfied with product performance during guarantee period, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Ste. 200, Baltimore, MD, 21224 for sales price refund. DAP is not liable for incidental or consequential damages.

50-Year Satisfaction Guarantee (Canada):

If purchaser is not satisfied with product performance during guarantee period, return used container and sales receipt to DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, Ontario M1X 1B7 for sales price refund. DAP Canada and its affiliates will not be liable for incidental, special or consequential damages under any circumstances.