



COOL KING® 5-Year Fibered Aluminum Roof Coating

Energy Saving Aluminum Sealant

- 5-Year Protection
- Bright Aluminum Color
- Saves Energy Costs



Manufacturer:

JETCOAT
472 Brehl Avenue
Columbus, Ohio
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

Description

A blend of pure waterproofing asphalt and high grade aluminum pigments plus the addition of fibers. Reflects up to 80% of the sun's rays, helping prevent excessive drying and cracking of substrate, thus reducing leaks. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, inside heat is reflected back into the building, thus saving energy costs. Dries silver.

Uses

- Metal Roofs
- Weathered Asphalt
- Mobile Homes
- Built-Up Roofs

Surface Preparation

Repair all cracks, splits, and holes using JETCOAT Plastic Wet or Dry Roof Cement and Asphalt Coated Reinforcing Fabric, adhering to the directions on their label. Allow repairs to weather at least 30 days before coating. Clean surfaces thoroughly by brooming away dirt, dust and loose particulate. Remove all grease and oil using detergent and water, rinsing thoroughly. Broom away excess water and allow to dry completely.

Application

Mix coating thoroughly before and during application. Uniformly coat the entire surface with the coating using a roofing brush or roller. Do not apply to wet or damp surfaces. Do not apply to roofs which hold water. Standing water will result

in premature failure.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean up with waterless hand cleaner immediately after use.

Weather Conditions

- Do not apply if rain or heavy dew is expected within 24 hours of application.
- Do not apply if temperature is expected to fall below 50 °F within 12 hours of application.

Coverage (Approximate)

- Metal Roofs: 75-100 sq. ft. per gallon
- Composition Roofs: 50-75 sq. ft. per gallon

Precautions

- Do Not Heat Or Thin
- Do Not Store At Temperatures Above 100 °F
- Combustible. Contains Petroleum Distillate

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 500 gm/liter max
- Use With Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

Cool King® 5-Year Fibered Aluminum Roof Coating
Energy Saving Aluminum Sealant

Form No.: JC-TD65215

Packaging

Item #	Container Size	Pack	Weight
65215	4.75 Gallon Pail	1	49 lbs.
65211	.9 Gallon Pail	6	58 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Asphalt	8052-42-4
Stoddard Solvent	64742-88-7
Aluminum Flake	7429-90-5
Cellulose	9004-34-6
Calcium Carbonate	1317-65-3