

#52 SPRAY ADHESIVE®



RCD Corporation's #52 Spray Adhesive® is formulated to bond insulation to galvanized and aluminum sheet metals. This adhesive has low soak-in properties and bonds to a variety of construction surfaces - from paper to metal. Our handy and compact 20 oz. aerosol can is portable, eliminates expensive application equipment, the time consuming clean-up process and saves valuable floor space too. Wide web spray pattern allows greater coverage in less time. A whole lot of value in one small can.

SPECS:

Catalog Number	300520	20 fl. oz. aerosol can; contains 17 fl. oz. of adhesive
Storage temperature	45° F to 90° F	
Shelf life	12 months (unopened container)	
Packaging	12 cans/box	
VOC Content	Less than 54% by weight. Qualifies for LEED Credits	

- Fast Tacking
- Wide Webbing Spray Pattern
- VOC Compliant
- Zero Chlorinated Solvents
- Earns LEED Credits

APPLICATION

RCD's #52 Spray Adhesive® works best at room temperatures. Shake can for at least one minute prior to spraying. Surfaces must be free from corrosion, dirt, grease, mold, mildew, oil and water. Hold can upright and point valve toward surface and spray from a distance of 6 to 8 inches, apply a light film while moving the can to avoid build up on the substrate.

Temporary Bond: Spray a light film on one surface only.

Permanent Bond: Spray both surfaces to be bonded. Allow time to tack, then bond. Testing of product parts in typical operating environments for compatibility and performance is recommended.

Cleaning Spray Tip: When finished with your application, turn the can upside down and spray for two seconds to clear valve. This prevents clogging the actuator. If adhesive has accumulated around the nozzle, wipe it clear while still wet. If adhesive is dried in valve opening, remove with degreasing solvent.

**Keep out of reach of children.
If there is contact with eyes, flush with clean water and contact physician.**

PRECAUTIONS

It is the applicator's responsibility for the design, use and storage of all building materials including #52 Spray Adhesive®. Store at temperatures between 45°F to 90°F. Rotate inventory using FIFO method. Protect from freezing. Do not apply below 38°F, or above 120°F. Apply #52 Spray Adhesive® only where the system operating temperatures will not exceed the service temperature limits of -20°F, to 185°F. Occupants, who are chemically sensitive, prone to allergic reactions and/or asthma, or have respiratory ailments of any kind, should not be exposed to aerosol products without consulting their physician for approval.

DANGER-Contents Flammable and under pressure. Vapors may ignite easily. Keep away from heat, sparks and open flames. Turn off pilot lights, heaters, electric motors and other sources of ignition. Use with good ventilation. Avoid prolonged breathing of vapor or mist. Appropriate respiratory protection is required when using this product. Avoid contact with eyes and prolonged or repeated contact with skin. Do not puncture or incinerate container. Do not store in direct sunlight or at temperatures exceeding 120° F, as container may burst.

FIRST AID: Skin Contact: Wash affected areas with soap and water. Seek medical attention if irritation persists. **Eye Contact:** Flush eyes with clear water for at least 15 minutes. Seek medical attention if irritation persists. **Ingestion:** Do not induce vomiting. Seek medical attention immediately. **Inhalation:** Provide fresh air. Respire if needed. Seek medical attention immediately.

WARRANTY

RCD's #52 Spray Adhesive® is warranted to do the work for which it is designed as set forth above. All other warranties, express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose, are disclaimed. It is understood and agreed that seller's liability, whether in contract, tort, warranty, negligence, personal injury, wrongful death or otherwise, shall not exceed the return of the amount of the purchase price paid by the purchaser and under no circumstances shall seller be liable for special, indirect or consequential damages. The price paid for the product is consideration in limiting seller's liability.

RCD, Doug and specific product designations are all trademark protected symbols owned by RCD Corp