



UL181B TAPE

Product Description:

TVM's UL181B tape is UV resistant polypropylene (PP) tape coated with a cold weather adhesive. Hand tearable, thinner and tougher than traditional duct tapes, UL181B lasts longer and will not delaminate with age. TVM's UL181B provides easy application and superior performance and durability over a wide range of temperatures and environmental conditions.



Stock Items: UL181B TAPE

Size 2.5" X 180' Rolls/Case: 20
Part No. 15812

Features:

- Pressure-sensitive acrylic adhesive forms a bond that strengthens with time
- Maintains a continuous vapor barrier and insulation system
- Excels in high heat and humidity conditions
- Ideal for use on reflective insulation and metal connections
- Performs well over a wide temperature range

Property	UL181B TAPE	TEST METHOD
Thickness:	3.0 mils (0.003")	PSTC-133
Adhesion:	41 oz./inch	PSTC-101
Shear Strength	>168 hours	PSTC-107
Elongation:	150%	PSTC-131
Tensile Strength:	22 lbs./inch width	PSTC-131
Minimum Application Temperature:	-37°C (-35°F)	NA
Maximum Continuous Temperature:	128°C (260°F)	NA



CUSTOMER SERVICE and SALES

US 169 Jari Drive , Johnstown, PA 15904 CANADA 13383 Fourth Line, Acton ON
Phone: 1.866.484.4TVM (4886) Fax: 1.877.SEND.TVM (736.3886) Email: customerservice@tvmi.com
Technical Support: 1.888.TECH.TVM (832.4886)

