



UL181B TAPE

Product Description:

TVM's UL181B tape is UV resistant polypropylene (PP) tape coated with a cold weather adhesive. Hand tearable, thinner and tougher than traditional duct tapes, UL181B lasts longer and will not delaminate with age. TVM's UL181B provides easy application and superior performance and durability over a wide range of temperatures and environmental conditions.



Stock Items: UL181B TAPE

Size 2.5" X 180' Rolls/Case: 20
Part No. 15812

Features:

- Pressure-sensitive acrylic adhesive forms a bond that strengthens with time
- Maintains a continuous vapor barrier and insulation system
- Excels in high heat and humidity conditions
- Ideal for use on reflective insulation and metal connections
- Performs well over a wide temperature range

| Property | UL181B TAPE | TEST METHOD |
|---|--------------------|-------------|
| Thickness: | 3.0 mils (0.003") | PSTC-133 |
| Adhesion: | 41 oz./inch | PSTC-101 |
| Shear Strength | >168 hours | PSTC-107 |
| Elongation: | 150% | PSTC-131 |
| Tensile Strength: | 22 lbs./inch width | PSTC-131 |
| Minimum Application Temperature: | -37°C (-35°F) | NA |
| Maximum Continuous Temperature: | 128°C (260°F) | NA |



CUSTOMER SERVICE and SALES

US 169 Jari Drive , Johnstown, PA 15904 CANADA 13383 Fourth Line, Acton ON

Phone: 1.866.484.4TVM (4886)

Fax: 1.877.SEND.TVM (736.3886)

Email: customerservice@tvmi.com

Technical Support: 1.888.TECH.TVM (832.4886)

