



CPDS 1000 System

Constant Pressure Dispensing System



Tanks sold separately.

The Touch 'n Seal CPDS 1000 is an inexpensive, low maintenance dispensing mechanism that, when used according to manufacturer's directions, applies Class 1 fire retardant, thermal insulating and sound attenuating 2-component polyurethane spray foam.

Height	49 in (125 em)
Depth	33 in (84 em)
Width	24.5 in (62 em)
Foam Delivery Rate @ 160 psi	4.0 lbs (1.8 kg) / minute
Foam Delivery Rate @ 200 psi	5.5 lbs (2.5 kg) / minute
Maximum Hose Length	150 ft (46 m)
Power Source	120V, 15 amp
Alternate Power Sources	Pressurized Dry Nitrogen, Compressed Air
Foam Type	CP 750 FR, 2 Component, Fire Retardant, 1.75 PCF CP 1200 FR, 2 Component, Fire Retardant, 1.0 PCF

0112150 Dispensing System

0112151 Closed Cell Foam Tank

Two-Component Polyurethane Foam Kits

Portable, disposable and self-contained with color-coded, pre-connected hoses. These kits are available in sizes from 15-600 board feet and provide a quick consistent flow of foam that dries in under a minute. Foam expands 30X.

Touch 'n Seal Two Component Foam Kits are portable, self-contained dispensing systems. When used according to manufacturer's directions, these systems supply thermal insulating and sound attenuating 2-component polyurethane

spray foams. Touch 'n Seal spray foams are permanent and dry within minutes of application.

Touch 'n Seal Spray Foam Kits use disposable, pressurized chemical cylinders to dispense polyurethane spray foams eliminating the need for external air compressors, pumping equipment or dry nitrogen. These systems provide quick and easy foam application for repairs and renovations, new installations and production applications.



2-Component spray foam systems provide fast, even foam flow that cures in about 45 seconds, making it ideal for use on large gaps and on all surfaces.

Foam kits include applicator gun and 10' hose, and illustrated directions. Kits are self contained, portable, and disposable. Contains no CFC's, no urea formaldehyde.

Standard

0112119 2 Part, 15 Board Feet

0112101 2 Part, 110 Board Feet

0112102 2 Part, 200 Board Feet

0112104 2 Part, 600 Board Feet

Fire Retardant

ASTM E84 rating: flame spread 15, smoke developed 10.

0112107 2 Part, 200 Board Feet

0112108 2 Part, 600 Board Feet

Replacement Nozzles

0112131 L Fan Nozzle Kit, Yellow
25/Box

0112132 Conical Nozzle Kit, Clear
25/Box